

# MAC FAUCETS

The World's Finest Selection of Designer & Commercial Automatic Faucets!

## Industry Standard™ Automatic Toilet Flush Valve



### **Models: ATV-2 Complete Valve**

(Valve and Stop (Less Spud) = ATV-2A)

(Valve Only (Less Spud and Stop) = ATV-2B)

#### Package Includes

Automatic Valve

1" Stop Valve

Wall Trim Kit

3/4"-9" Spud and  
Vacuum Breaker

Urinal Trim Kit

**Batteries Pre-installed**

All the hardware necessary  
for satisfactory installation

ASSI 1037

ANSI/ASME  
A112.19.6

Installation Conforms to  
ADA Requirement

### Featuring:

- Solid Brass Body.
- Solid Brass, Trouble Free Piston Valve.
- Battery Powered (4 Standard AA Batteries).
- Solid Brass Stop.
- 1-1/2", 9" Long Spud and Vacuum Breaker.
- \*\*\* Optional 15" long Spud and Vacuum Breaker.
- Hermetically Sealed Sensor and electronics.
- Visible Low Battery Indicator Built into Sensor Capsule.
- Available in 20 Finishes.

## SPECIFICATIONS AND DIMENSIONS

MODEL:	<b>ATV-2</b>
BODY:	SOLID BRASS
STOP:	SOLID BRASS
SPUD:	1-1/2", 9" LONG WITH VACUUM BREAKER
POWER:	4 AA ALKALINE BATTERIES
SOLENOID VALVE:	6 VOLT MAGNET LATCHING
WORKING WATER PRESSURE:	1 PSI -100 PSI
WATER INLET SIZE:	1" NPT FEMALE, AT STOP
WATER OUTLET SIZE:	1-1/2" NPS MALE
WATER FLOW CONTROL:	YES, AT STOP
FLUSH CYCLE:	1.6 GPF/6.0 LPF
VALVING SYSTEM:	POSTON TYPE
STRAINER:	50 MESH
SENSOR TYPE AND LOCATION:	ACTIVE INFRARED, BODY MOUNT
SENSOR MICROPROCESSOR:	DIGITAL, PUG AND PLAY
SENSING ZONE:	8" TO 32"

### All Dimensions in Inches

