

# MAC FAUCETS

The World's Finest Selection of Designer & Commercial Automatic Faucets!

## Industry Standard™ Faucet Line



**Model FA444-15**

### Featuring:

- Solid Brass Faucet.
- Solid Brass Operating Valve.
- Resin Encased Control Electronics.
- Battery powered, 4 standard AA batteries.
- Visible Low Battery Indicator.

#### Package Includes

Faucet

FA444 Automator

4" Center Installation  
Only

Single Water Source  
Fitting

Back Flow Preventers

Stainless Steel Hose

Mounting Hardware

Batteries Pre-installed

All the hardware necessary  
for satisfactory installation

(Optional)  
Mixing Valve, Factory  
Preset 50/50

ANSI A112.18.1M

CSA Standard B125,  
2.2 U.S. GPM

Complies with NSF  
Standard 61, Section 9

The model 15 is specially designed for sinks with faucet holes that are spaced **4" on center**. This model is ideal for applications where price is key consideration. Although the model 15 is in fact **THE BEST PRICED electronic faucet available on the market today**, this unique faucet is rated **HEAVY DUTY** and features the Faucet Automator model FA444HD. Manufactured to last, the FA444HD employs an **all in one sensor/electronic package**. This package is hermetically sealed with visible low battery indicator. Also employed is a **SOLID BRASS** solenoid valve that is specially designed for high traffic applications. The faucet is sold complete and ready to install.

## SPECIFICATIONS AND DIMENSIONS

MODEL:	<b>FA444-15HD</b>
SPOUT:	CHROME PLATED SOLID BRASS
POWER:	4 (AA) ALKALINE BATTERIES OR AC ADAPTER
BATTERY LIFE EXPECTANCY:	200,000 CYCLES
SOLENOID VALVE:	6 VOLT MAGNET LATCHING
WORKING WATER PRESSURE:	1 PSI -100 PSI
SUPPLY INLET SIZE:	1/2" NPT MALE
WATER TEMPERATURE CONTROL:	NONE
POP-UP DRAIN ROD:	NONE
SENSOR TYPE AND LOCATION:	ACTIVE INFRARED, NECK MOUNT
SENSOR MICROPROCESSOR:	DIGITAL, PUG AND PLAY
SENSING RANGE:	2" TO 6"
RESPONSE TIME:	0.6 SECOND
SHUT-OFF DELAY TIME:	2 SECOND
MAXIMUM RUNNING TIME:	60 SECONDS
PARTICLE FILTER SIZE:	50 MESH
AERATOR:	2.2 GPM STANDARD.

### Optional Equipment:

- Lavatory Drain, Grid and Pop-Up Type.
- Aerators: 1.5GPM, 0.5GPM, 0.5GPM Vandal Resistant Aerator
  - Adjustable & Nonadjustable Under the Sink Mixing Valve.
  - AC Adapters.

All Dimensions in Inches

