

# MAC FAUCETS

The World's Finest Selection of Designer & Commercial Automatic Faucets!

## Industry Standard™ Faucet Line



**Model: FA444-31**

Featuring:

- Solid Brass Faucet.
- Solid Brass Operating Valve.
- 360° rotating neck.
- Resin Encased Control Electronics.
- Battery powered, 4 standard AA batteries.
- Visible Low Battery Indicator.

### Package Includes

Faucet

FA444 Automator

Single Water Source  
Fitting

Back Flow Preventers

Stainless Steel Hose

Mounting Hardware

**Batteries Pre-installed**

All the hardware necessary  
for satisfactory installation

**(Optional)**  
**Mixing Valve, Factory**  
**Preset 50/50**

ANSI A112.18.1M

CSA Standard B125,  
2.2 U.S. GPM

Complies with NSF  
Standard 61, Section 9

### Optional Equipment:

- Lavatory Drain, Grid and Pop-Up Type.
- Deck Plates for 4" and 8" sinks.
- Adjustable & Nonadjustable Under The Sink Mixing.
- AC Adapters.
- Matching Above The Sink Water Mixing Valve.
- Matching Soap Dispenser.
- Matching Hole Cap Cover.
- Matching Off-Body Pop-Up Lift.

## SPECIFICATIONS AND DIMENSIONS

MODEL:	<b>FA444-31</b>
SPOUT:	BASE: SOLID BRASS. GOOSENECK: BRASS.
POWER:	4 (AA) ALKALINE BATTERIES OR AC ADAPTER
BATTERY LIFE EXPECTANCY:	200,000 CYCLES
SOLENOID VALVE:	6 VOLT MAGNET LATCHING
WORKING WATER PRESSURE:	1 PSI - 100 PSI
SUPPLY INLET SIZE:	1/2" NPT MALE
WATER TEMPERATURE CONTROL:	OPTIONAL
POP-UP DRAIN ROD:	OPTIONAL
SENSOR TYPE AND LOCATION:	ACTIVE INFRARED, NECK MOUNT
SENSOR MICROPROCESSOR:	DIGITAL, PUG AND PLAY
SENSING RANGE:	2" TO 6"
RESPONSE TIME:	0.3 SECOND
SHUT-OFF DELAY TIME:	2 SECONDS
MAXIMUM RUNNING TIME:	60 SECONDS
PARTICLE FILTER SIZE:	50 MESH
AERATOR:	2.2 GPM STANDARD 0.5 GPM OPTIONAL

**All Dimensions in Inches**

