

MAC FAUCETS

The World's Finest Selection of Designer & Commercial Automatic Faucets!

Industry Standard™ Faucet Line



Model: FA444-43 Vessel Sink Applications

Featuring:

- Non Rotating Neck
- Solid Brass Faucet.
- Solid Brass Operating Valve.
- Resin Encased Control Electronics.
- Battery powered, 4 standard AA batteries.
- Visible Low Battery Indicator.

Package Includes

Faucet

FA444 Automator

Single Water Source
Fitting

Back Flow Preventers

Stainless Steel Hose

Mounting Hardware

Batteries Pre-installed

All the hardware necessary
for satisfactory installation

(Optional)
Mixing Valve, Factory
Preset 50/50

ANSI A112.18.1M

CSA Standard B125,
2.2 U.S. GPM

Complies with NSF
Standard 61, Section 9

SPECIFICATIONS AND DIMENSIONS

MODEL:	FA444-43
SPOUT:	ALL BRASS, NONE ROTATING
POWER:	4 (AA) ALKALINE BATTERIES OR AC ADAPTER
BATTERY LIFE EXPECTANCY:	200,000 CYCLES
SOLENOID VALVE:	6 VOLT MAGNET LATCHING
WORKING WATER PRESSURE:	1 PSI -100 PSI
SUPPLY INLET SIZE:	1/2" NPT MALE
WATER TEMPERATURE CONTROL:	OPTIONAL
POP-UP DRAIN ROD:	N/A
SENSOR TYPE AND LOCATION:	ACTIVE INFRARED, SPOUT MOUNT
SENSOR MICROPROCESSOR:	DIGITAL, PUG AND PLAY
SENSING RANGE:	2" TO 6"
RESPONSE TIME:	0.3 SECOND
SHUT-OFF DELAY TIME:	2 SECONDS
MAXIMUM RUNNING TIME:	60 SECONDS
PARTICLE FILTER SIZE:	50 MESH
AERATOR:	2.2 GPM STANDARD 0.5 GPM OPTIONAL

All Dimensions in Inches

