

MAC FAUCETS

The World's Finest Selection of Designer & Commercial Automatic Faucets!

Industry Standard™ Faucet Line



Model: FA610-65

Featuring:

- **Splash Mount Faucet.**
- All Brass Construction.
- Battery Powered, 4 Standard AAA Batteries.
- Rotating Neck.
- Hermetically Sealed Sensor and Electronics.
- Visible Low Battery Indicator.
- Battery Replacement Accessible From Above Sink.
- Filter Clean-out Accessible from above sink.
- Water Flow Adjustment Accessible from above sink.

Package Includes

Faucet

FA610 Automator

Single Water Source
Fitting

Back Flow Preventers

Stainless Steel Hose

Mounting Hardware

Batteries Pre-installed

All the hardware necessary
for satisfactory installation

(Optional)
**Mixing Valve, Factory
Preset 50/50**

ANSI A112.18.1M

CSA Standard B125,
2.2 U.S. GPM

Complies with NSF
Standard 61, Section 9

SPECIFICATIONS AND DIMENSIONS

MODEL:	FA610-65
SPOUT:	BASE: SOLID BRASS. GOOSE NECK: BRASS.
POWER:	4 (AAA) ALKALINE BATTERIES
BATTERY LIFE EXPECTANCY:	150,000 CYCLES
SOLENOID VALVE:	6 VOLT MAGNET LATCHING
WORKING WATER PRESSURE:	1 PSI -100 PSI
SUPPLY INLET SIZE:	1/2" NPT MALE
WATER TEMPERATURE CONTROL:	OPTIONAL
POP-UP DRAIN ROD:	N/A
SENSOR TYPE AND LOCATION:	ACTIVE INFRARED, NECK MOUNT
SENSOR MICROPROCESSOR:	DIGITAL, PUG AND PLAY
SENSING RANGE:	2" TO 6"
RESPONSE TIME:	0.3 SECOND
SHUT-OFF DELAY TIME:	1 SECONDS
MAXIMUM RUNNING TIME:	60 SECONDS
PARTICLE FILTER SIZE:	50 MESH
AERATOR:	2.2 GPM STANDARD. 0.5 GPM OPTIONAL

All Dimensions in Inches

